

IB 04/00654

REC'D 18 MAY 2004

USPO

PCT

PA 1147683

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

March 29, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 60/496,854


FILING DATE: August 21, 2003

PCT/IB04/00654

**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS



L. Edelen

L. EDELEN
Certifying Officer

BEST AVAILABLE COPY

08/21/03

16711 U.S. PTO

PTO/SB/16 (08-03)

Approved for use through 07/31/2003. OMB 0851-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.**PROVISIONAL APPLICATION FOR PATENT COVER SHEET**

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

Express Mail Lab IN EV 317506474 US

22154 U.S. PTO
60/496854

INVENTOR(S)					
Given Name (first and middle [if any])	Family Name or Surname	Residence (City and either State or Foreign Country)			
Johan Pieter Wilhelmina Paul	de Wet Jansen Jacobson	Vanderbijlpark, South Africa Vanderbijlpark, South Africa Sasolburg, South Africa			
<input type="checkbox"/> Additional inventors are being named on the _____ separately numbered sheets attached hereto					
TITLE OF THE INVENTION (500 characters max)					
Extraction Of Oxygenates From A Hydrocarbon Stream					
Direct all correspondence to: CORRESPONDENCE ADDRESS					
<input type="checkbox"/> Customer Number 					
OR					
<input checked="" type="checkbox"/> Firm or Individual Name		Browning Bushman P.C.			
Address		5718 Westhelmer			
Address		Suite 1800			
City		Houston	State	Texas	ZIP 77057-5771
Country		U.S.A.	Telephone	713-266-5593	Fax 713-266-5169
ENCLOSED APPLICATION PARTS (check all that apply)					
<input checked="" type="checkbox"/> Specification		Number of Pages	13	<input type="checkbox"/> CD(s), Number	
<input checked="" type="checkbox"/> Drawing(s)		Number of Sheets	1	<input type="checkbox"/> Other (specify)	
<input type="checkbox"/> Application Data Sheet. See 37 CFR 1.76					
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT					
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.				FILING FEE AMOUNT (\$)	
<input checked="" type="checkbox"/> A check or money order is enclosed to cover the filing fees				<div style="border: 1px solid black; padding: 5px; text-align: center;">\$160.00</div>	
<input checked="" type="checkbox"/> The Director is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number 02-4345					
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached.					
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
<input checked="" type="checkbox"/> No.					
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____					

Respectfully submitted,

SIGNATURE

TYPED or PRINTED NAME C. James Bushman, Attorney

713-266-5593

TELEPHONE

Date 08-21-03

REGISTRATION NO.

24,810

(if appropriate)


Docket Number:

Sasol S.A.- 6

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the completed application to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Mail Stop Provisional Application

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

CERTIFICATE OF MAILING BY "EXPRESS MAIL" (37 CFR 1.10)			Docket No.
Applicant(s): Johan Pieter de Wet, Wilhelmina Jansen and Paul Jacobson			Sasol S.A.- 6
Serial No. To Be Assigned	Filing Date Herewith	Examiner To Be Assigned	Group Art Unit To Be Assigned
Invention: Extraction Of Oxygenates From A Hydrocarbon Stream			
<p>I hereby certify that this <u>Provisional Patent Application and all related documents</u> <i>(Identify type of correspondence)</i></p> <p>is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 in an envelope addressed to: The Commissioner of Patents and Trademarks, Washington, D.C. 20231-0001 on <u>August 21, 2003</u> <i>(Date)</i></p> <p style="text-align: right;"><u>Sheri Cooper</u> <i>(Typed or Printed Name of Person Mailing Correspondence)</i></p> <p style="text-align: right;"><u></u> <i>(Signature of Person Mailing Correspondence)</i></p> <p style="text-align: right;"><u>EV 317506474 US</u> <i>("Express Mail" Mailing Label Number)</i></p>			
<p style="text-align: center;">Note: Each paper must have its own certificate of mailing.</p>			

PATENT APPLICATION SERIAL NO. _____

U.S. DEPARTMENT OF COMMERCE
PATENT AND TRADEMARK OFFICE
FEE RECORD SHEET

07/14/98 FEE 00000001 00195851
150.00 C

PTO-1556
(5/87)

EXTRACTION OF OXYGENATES FROM A HYDROCARBON STREAM

BACKGROUND OF THE INVENTION

This invention relates to a method for extracting oxygenates from a hydrocarbon stream.

Many methods for extracting oxygenates from hydrocarbon streams are known. Such extraction methods include hydrogenation, azeotropic distillation, extractive distillation, vapour phase dehydration, liquid phase dehydration and liquid-liquid extraction.

This invention relates to a process for extracting or separating oxygenates from the condensation product of a low temperature Fischer-Tropsch reaction, to produce a condensation product that is particularly suitable for the production of linear alkyl benzene.

SUMMARY OF THE INVENTION

According to the invention there is provided a method for extracting oxygenates from the condensation product of a low temperature Fischer-Tropsch reaction, while preserving the olefin content of the condensation product. The condensation product typically contains 15% to 30% by weight olefins, usually 15% to 25% by weight olefins, 60% to 80% by weight paraffins and 5% to 10% by weight oxygenates.

The oxygenate extraction process is a liquid-liquid extraction process that preferably takes place in an extraction column using a polar organic solvent, preferably methanol, and water as the solvent, wherein the polar organic solvent and water are added separately to the extraction column.

The hydrocarbon stream is fed into the extraction column at, or near, the bottom thereof, a polar organic solvent stream is fed into the extraction column at, or near, the top thereof, and a water stream is fed into the extraction column between the hydrocarbon stream and polar organic solvent stream.

An extract from the liquid-liquid extraction may be sent to a solvent recovery column from which a tops product comprising polar organic solvent, olefins and paraffins is recycled to the extraction column, thereby enhancing the overall recovery of olefins and paraffins. A bottoms product from solvent recovery column may also be recycled to the extraction column.

A raffinate stream from the extraction column is preferably sent to a stripper column from which a hydrocarbon stream containing more than 90% by weight olefins and paraffins and typically less than 0.2% by weight, preferably less than 0.02% by weight, most preferably less than 0.01% by weight oxygenates exits as a bottoms product.

The solvent preferably has a water content of more than 3% by weight, more preferably a water content of about 5% - 15% by weight.

BRIEF DESCRIPTION OF THE DRAWING

The Figure is a block diagram of a process of the invention for extracting oxygenates from a hydrocarbon stream.

DESCRIPTION OF PREFERRED EMBODIMENTS

This invention relates to a process for extracting oxygenates from a hydrocarbon condensate stream from a low temperature Fischer-Tropsch reaction. The substantially oxygenate-free hydrocarbon stream can be used in the production of linear alkyl benzene.

In the Fischer-Tropsch process, synthesis gas (carbon monoxide and hydrogen) obtained either from the gasification of coal or the reforming of natural gas, is reacted over a Fischer Tropsch catalyst to produce a mixture of hydrocarbons ranging from methane to waxes and smaller amounts of oxygenates.

In a low temperature Fischer-Tropsch reaction, the reaction takes place in a slurry bed reactor or fixed bed reactor, preferably a slurry bed reactor, at a temperature in the range of 160°C - 280°C, preferably 210°C - 260°C, and a pressure in the range of 18-50 bar (gauge), preferably between 20-30 bar (gauge), in the presence of a catalyst. The catalyst may include iron, cobalt, nickel or ruthenium. However, a cobalt-based catalyst is preferred for the low temperature reaction. Usually, the cobalt catalyst is supported on an alumina support.

During the Fischer-Tropsch reaction, a lighter hydrocarbon vapour phase is separated from a liquid phase comprising heavier liquid hydrocarbon products. The heavier liquid hydrocarbon product (waxy products) is the major product of the reaction and may, for example, be hydrocracked to produce diesel and naphtha.

The lighter hydrocarbon vapour phase which comprises gaseous hydrocarbon products, unreacted synthesis gas and water is condensed to provide a "condensation product" which comprises an aqueous phase and a hydrocarbon condensation product phase.

The hydrocarbon condensation product includes olefins, paraffins in the C_4 to C_{26} range, and oxygenates including alcohols, esters, aldehydes, ketones and acids.

Typically, a hydrocarbon condensation product for a low temperature Fischer-Tropsch reaction contains 15%-30% by weight olefins, 60%-80% by weight paraffins, and 5%-10% by weight oxygenates. It has, surprisingly, been found that even though this condensation product has a low olefin content, it can be used in the production of linear alkyl benzene. However, it is necessary to first extract the oxygenates as these species have a negative effect on the alkylation reaction. There is therefore a need to find a process for extracting oxygenates, but at the same time preserve the olefin concentration. For the production of linear alkyl benzene, the hydrocarbon condensate product is fractionated into a C_{10} – C_{13} cut which, by way of example, contains 25% by weight olefins, 68% by weight paraffins and 7% by weight oxygenates.



In the prior art, many methods of extracting oxygenates from hydrocarbon streams are suggested. Such removal methods include hydrogenation, azeotropic distillation, extractive distillation, vapour phase dehydration, liquid phase dehydration and liquid-liquid extraction. It has been found that liquid-liquid extraction is a preferred method of oxygenate extraction because, if the correct solvent is selected, the olefin concentration can be preserved. In liquid-liquid extraction, the solvent can be any polar material that has partial miscibility with the feed stream 14, such as tri-ethanol amine, tri-ethylene glycol with between zero and 20% water, acetonitrile with between 5% and 20% water, acetol, diols, methanol, or ethanol and water.

According to the invention, a preferred solvent in a liquid-liquid extraction column is a polar organic solvent, in this case methanol, and water. Usually, this type of solvent would be added as a mixture at the top of the liquid-liquid extraction column. It has been found that it is possible to obtain a higher recovery of olefins and paraffins, with a lower oxygenate content

(i.e. a purer product) by adding the polar organic solvent and the water separately to the liquid-liquid extraction column.

Another aspect of the invention is that, normally, a high-boiling point solvent is preferred because the solvent recovery steps after extraction require less energy than will be the case for a low-boiling point solvent. However, it has been found that a mixture of methanol and water, which is a low-boiling point solvent, need not suffer from this drawback, because it can be effective at low solvent to feed ratios (this can be lower than 1 if the required oxygenate extraction is not too severe). Furthermore, one would not expect to be able to use methanol and water as a solvent in a liquid-liquid extraction column to extract oxygenates from the abovementioned hydrocarbon condensate because a study of the different azeotropes with water that exist in the hydrocarbon condensate would lead one to expect that it would not be possible to distil water in a solvent recovery column without azeotroping oxygenates overhead as well. Surprisingly, this turns out not to be the case.

A further aspect of the invention is that it has been found that a water/methanol solvent, preferably with greater than 3% by weight water content in the liquid-liquid extraction column leads to better recovery of desired products in the solvent recovery column than a dry methanol solvent or a water/methanol solvent with less than 3% by weight water in the liquid-liquid extraction column. This is shown in Graph 1 below, from which it can be seen that a methanol/water solvent with 5% by weight water provides as much as 80% recovery of olefins and paraffins in the solvent recovery column. Graph 2 below shows that almost a 100% recovery of C10/C11 olefins and paraffins in the solvent recovery column is possible.

Graph 1**Graph 2**

Thus, according to the invention, typically 90% of the olefins and paraffins are recovered from the liquid-liquid extraction column. The 10% of olefins and paraffins not recovered are sent to the solvent recovery column in the extract from the liquid-liquid extraction column. Up to 60% of the olefins and paraffins in the solvent recovery column are recovered in the overheads product from the solvent recovery column and recycled to the liquid-liquid extraction column. This results in an over-all recovery of olefins and paraffins of more than 90%.

With reference to the Figure, a liquid-liquid extraction process of the invention includes a liquid-liquid extraction column 20. The fractionated condensation product of a low temperature Fischer-Tropsch reaction described above 14 is fed into the extraction column 20 at, or near, the bottom thereof. The solvent for the extraction column 20 is water and methanol. According to the invention, the water and methanol are added to the extraction column 20 separately. Methanol is added to the extraction column 20 via a methanol stream 21 at, or near, the top of the extraction column 20. Water is added to the extraction column 20 via a water stream 34 located between the hydrocarbon stream 14 and methanol stream 21. The flow of methanol and water is controlled to provide a solvent in the column with more than 5% by weight water. The solvent to feed ratio in the extraction column 20 is low, typically less than 1.5.

Raffinate 22 from the top of the extraction column 20, which includes olefins and paraffins and a small amount of solvent, enters a raffinate stripper column 23 and a hydrocarbon product stream comprising more than 90% by weight olefins and paraffins and less than 0.01% by weight oxygenates exits as a bottoms product 24. The bottoms product 24, which shows an overall recovery of over 90% of the olefins and paraffins, contains more than 20% by weight α -olefins and more than 70% by weight n-paraffins. Thus, the olefin content of the hydrocarbon product (which is intended for use in the production of linear alkyl benzene) has been preserved. A solvent comprising mainly methanol (more than 90% by weight) and low concentrations of water (less than 5% by weight) and olefins/paraffins (less than 5% by weight) exits as a tops product 25 and is returned to the solvent feed stream 21. If it is desired to recover the bottoms product 24 as a vapour stream, this can be done by taking a bottoms vapour stream from the column 20. The liquid product from the column 20 will then be a very small effluent stream.

An extract 26 is drawn from the bottom of the extraction column 20 and is fed to a solvent recovery column 27. A tops product 29 from the solvent recovery column 27 comprises over 90% by weight methanol and 2% by weight olefins and paraffins. Up to 60% of the olefins and paraffins from the extract 26 are recovered to the tops product 29. The tops product is then recycled to the solvent stream 21. The oxygenate content of the tops product 29 can be as low as 50 ppm, depending on the solvent to feed ratio used in the extraction column 20. A bottoms product 28 from the solvent recovery column 27 comprises mainly water, oxygenates and olefins/paraffins. This bottoms product 28 forms two liquid phases that can be decanted in a decanter 30. The organic phase is an oxygenate, olefin and paraffin stream 31, which leaves the process as a product. The aqueous phase is a stream 32, which is recycled to the extraction column 20 via the water stream 34.

The presence of water in the extraction column 20 improves the recovery of paraffins and olefins in the raffinate stream 22. Although it is important for the water to be present in the lower section of the extraction column 20, including the point where the extract 26 is drawn from the extraction column 20, it has been found that it is not necessary for the water to be present throughout the extraction column 20. It has also been found that it is beneficial to have as little water as possible at the top of the extraction column 20 as the presence of water lowers the methanol's ability to take up oxygenates which would result in a higher solvent to feed ratio when compared to dry methanol. Thus, if as little water as possible is present in the upper section of the extraction column 20 it is beneficial in that it is possible to use a lower solvent to feed ratio than when water is added as a mixture together with methanol. Adding the water separately into the extraction column 20 between the hydrocarbon stream 14 and methanol stream 21 results in an improved paraffin and olefin recovery with better raffinate 22 purity, than if the water and methanol were added as a mixture. As mentioned above, the aqueous phase stream 32 recovered from the decanter 30 is recycled to the water stream 34 into the extractor column 20. The stream 32 may contain oxygenates and the addition of this water at a

different point to the methanol stream 21 lower down the extraction column 20 ensures that oxygenates are cleaned from the stream in the column, before they can appear in the raffinate stream 22.

With reference to Comparative Example 1 and the Example 2 of the invention below, it is evident that the process of the invention where the water and methanol are added separately leads to a lower oxygenate content in the product stream 24. Example 2 provides an oxygenate content of 0.0094% by weight in the product stream 24, while comparative Example 1 provides an oxygenate content of 0.0145% by weight in the product stream 24. Thus the product of Example 2 of the invention provides a more suitable hydrocarbon feed stream for use in the production of linear alkyl benzene. Example 2 of the invention also shows a higher overall olefin and paraffin recovery than comparative Example 1.

The invention will now be described in more detail with reference to the following non-limiting Example 2 and comparative Example 1.

Comparative Example 1

This example shows a comparative process where the water and methanol are introduced to the extraction column together in the solvent feed stream 21, and the stream 32 is recycled to the solvent feed stream 21. The extraction column 20 was run at a solvent to feed ratio of 1.25 and a temperature of 50°C. The overall olefin/paraffin recovery in the stream 24 was 89.9%, with an α -olefin concentration of 21.6% by weight, n-paraffin concentration of 72.2% by weight and 0.3% by weight branched hydrocarbons and 5.9% by mass internal olefins.

Extraction column 20

Stream	14		21		22		26	
	Comp (wt%)	Flow (kg/hr)	Comp (wt%)	Flow (kg/hr)	Comp (wt%)	Flow (kg/hr)	Comp (wt%)	Flow (kg/hr)
Total	100	3000	100	3750	100	2530	100	4220
Total C10-C13 P/O	92.7	2779.7	2.16	81.0	99.1	2507.9	6.20	261.7
Total Oxygenates	7.3	217.7	0.000	0.000	0.0144	0.365	5.78	243.7
Lights and Heavies	0.057	1.7	0.004	0.144	0.0104	0.263	0.00480	0.202
Water	0.031	0.934	6.01	225.6	0.0073	0.184	5.74	242.4
Methanol	0.000	0.000	91.7	3443.3	0.842	21.31	82.3	3472.0

Raffinate Stripper column 23

Stream	22		25		24	
	Comp (wt%)	Flow (kg/hr)	Comp (wt%)	Flow (kg/hr)	Comp (wt%)	Flow (kg/hr)
Total	100	2530	100	30	100	2500
Total C10-C13 P/O	99.1	2507.9	2.63	0.793	99.97	2499.4
Total Oxygenates	0.0144	0.365	0.00163	0.000491	0.0145	0.363
Lights and Heavies	0.0104	0.263	0.0887	0.0267	0.00808	0.202
Water	0.0073	0.184	1.52	0.456	0.00115	0.0288
Methanol	0.842	21.31	95.4	28.7	0.000	0.000

Solvent Recovery column 27

Stream	26		29		28	
	Comp (wt%)	Flow (kg/hr)	Comp (wt%)	Flow (kg/hr)	Comp (wt%)	Flow (kg/hr)
Total	100	4220	100	3584	100	636
Total C10-C13 P/O	6.20	261.7	2.37	85.1	27.6	175.8
Total Oxygenates	5.78	243.7	0.00140	0.0503	42.0	267.0
Lights and Heavies	0.00480	0.202	0.00747	0.268	0.00279	0.0177
Water	5.74	242.4	1.30	46.8	29.3	186.6
Methanol	82.3	3472.0	96.2	3451.9	1.04	6.63

Example 2

This example shows a process according to the invention where the methanol and water are introduced to the extraction column in separate streams 21 and 34 respectively. The extraction column 20 was run at a solvent to feed ratio of 1.2 and a temperature of 50°C. The overall olefin/paraffin recovery in the stream 24 was 92.3%, with an α -olefin concentration of 21.6% by weight, n-paraffin concentration of 72.2% by weight and 0.3% by weight branched hydrocarbons and 5.9% by weight internal olefins.

Extraction column 20

Stream	14		34		21		22		26	
	Comp (wt%)	Flow (kg/hr)	Comp (wt%)	Flow (kg/hr)	Comp (wt%)	Flow (kg/hr)	Comp (wt%)	Flow (kg/hr)	Comp (wt%)	Flow (kg/hr)
Total	100	3000	100	179	100	3334	100	2599	100	3914
Total C10-C13 P/O	92.6	2778.8	0.000	0.000	2.11	70.3	99.0	2572.1	7.89	308.8
Total Oxygenates	7.34	220.3	0.000	0.000	0.000	0.000	0.00937	0.244	6.00	234.9
Lights and Heavies	0.0156	0.470	0.000	0.000	0.009	0.298	0.00292	0.0758	0.00813	0.318
Water	0.0164	0.492	94.9	169.9	0.29	9.7	0.00270	0.0702	4.89	191.4
Methanol	0.000	0.000	5.07	9.07	97.6	3253.7	1.02	26.5	81.2	3178.6

Raffinate Stripper column 23

Stream	22		25		24	
	Comp (wt%)	Flow (kg/hr)	Comp (wt%)	Flow (kg/hr)	Comp (wt%)	Flow (kg/hr)
Total	100	2599	100	33	100	2566
Total C10-C13 P/O	99.0	2572.1	2.01	0.663	99.98	2565.73
Total Oxygenates	0.00937	0.244	0.00647	0.00213	0.0094	0.24122
Lights and Heavies	0.00292	0.0758	0.0708	0.0234	0.000488	0.0125
Water	0.00270	0.0702	0.210	0.0693	0.000500	0.0128
Methanol	1.02	26.5	97.7	32.2	0.000	0.0

Solvent Recovery column 27


Stream	26		29		28	
	Comp (wt%)	Flow (kg/hr)	Comp (wt%)	Flow (kg/hr)	Comp (wt%)	Flow (kg/hr)
Total	100	3914	100	3171	100	743
Total C10-C13 P/O	7.89	308.8	2.01	63.8	34.8	258.4
Total Oxygenates	6.00	234.9	0.00335	0.1	32.9	244.8
Lights and Heavies	0.00813	0.318	0.00237	0.075	0.00869	0.0646
Water	4.89	191.4	0.22	7.0	28.7	213.6
Methanol	81.2	3178.6	97.8	3100.0	3.51	26.09

CLAIMS

1. A method of extracting oxygenates from a hydrocarbon stream using an extraction solvent comprising a polar organic solvent and water, wherein the polar organic solvent and water are added separately in the extraction method.
2. The method according to claim 1 wherein the hydrocarbon stream is the hydrocarbon condensation product of a low temperature Fischer-Tropsch reaction.
3. The method according to claim 2, wherein, prior to extraction, the hydrocarbon condensation product contains 15% to 30% by weight olefins, 60% to 80% by weight paraffins and 5% to 10% by weight oxygenates.
4. The method according to claim 1, wherein liquid-liquid extraction takes place in a liquid extraction column and the polar organic solvent and water are added separately to the column.
5. The method according to claim 4 wherein the hydrocarbon stream is fed into the extraction column at, or near, the bottom thereof, a polar organic solvent stream is fed into the extraction column at, or near, the top thereof, and a water stream is fed into the extraction column between the hydrocarbon stream and polar organic solvent stream.
6. The method according to claim 5, wherein a raffinate from the extraction column is sent to a raffinate stripper column from which a hydrocarbon feed stream containing olefins and paraffins and less than 0.2% by weight oxygenates exits as a bottoms product.
7. The method according to claim 6, wherein a raffinate from the extraction column is sent to a raffinate stripper column from which a

hydrocarbon feed stream containing olefins and paraffins and less than 0.02% by weight oxygenates exits as a bottoms product.

8. The method according to claim 7, wherein a raffinate from the extraction column is sent to a raffinate stripper column from which a hydrocarbon feed stream containing olefins and paraffins and less than 0.01% by weight oxygenates exits as a bottoms product.
9. The method according to claim 4 wherein an extract from the liquid-liquid extraction is sent to a solvent recovery column from which a tops product comprising polar organic solvent, olefins and paraffins is recycled to the extraction column, thereby enhancing the overall recovery of olefins and paraffins.
10. The method according to claim 1 wherein the polar organic solvent is methanol.
11. The method according to claim 10 wherein the extraction solvent has a water content of more than 3% by weight.
12. The method according to claim 11 wherein the extraction solvent has a water content of about 5% - 15% by weight.



This Page is inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLORED OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REPERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images
problems checked, please do not report the
problems to the IFW Image Problem Mailbox**